

DRAWN DATE
OGK 10-24-98

CHECKED

APPROVED



415 EAST DUNDEE
OTTAWA, KANSAS 66067
PHONE (785) 242-2200
FAX (785) 242-6117

SHEET

1 OF 1

ENGINEERING SPECIFICATIONS OR INSTRUCTIONS

ESN-0026

STANDARD SPECIFICATION FOR:

**SAE 1008 GREATER THEN .230 INCH SHEET,
LOW ALLOY, HOT ROLLED COMMERCIAL QUALITY**

DESCRIPTION:

SAE 1008, COMMERCIAL QUALITY, HOT ROLLED
LOW CARBON SHEET, PICKLED AND OILED,
TEMPER ROLLED, CUT OR MILL EDGE

SPECIFICATION REFERENCE:

SAE 1008
ASTM A635-96

MECHANICAL PROPERTIES:

YIELD POINT - 30 KSI MIN.
ELONGATION IN 2 INCHES - >25%
PER ASTM A370

FOR COMPLETE CHEMICAL AND PHYSICAL
REQUIREMENTS SEE ASTM A 635-96

FOR DIMENSIONAL AND OTHER REQUIREMENTS
SEE ASTM A6/A6M

A 981880 11-24-98

ESN-0026 PG 1 OF 1